

CENTURY[®]

Express Series



Composite body and optional equipment shown.

- *16,000 lb. Recovery Boom*
- *7,500 lb. Tow Rating*
- *Modular Body Design*
- *Designed for Superior Visibility*
- *Spacious Tool Compartments*

millерind.com



Standard Features

- 60" C.A. Steel Modular Body
- Adjustable Body Width, 88" or 94"
- Integrated Boom & Wheel Lift System
- Hydraulic Auto-load Crossbar
- In-Cab Remote Control Pendant on Cord with 8 Functions
- Dual Manual Controls
- 1 Pair of Safety Straps
- Safety Chains in Rear Pockets
- Tool Compartment, Left & Right Hand Side
- Power Boom Elevation with Holding Valve
- 8,000 lb. Variable Speed Hydraulic Winch (Dual Winches on the 312)
- 3/8" x 100' Cable Assembly
- 360° Directional Boom End Swivel
- Winch Cable Tensioner & Free Spool Handles
- Federal Standard #108 Lighting
- Wiring Harness with Junction Box
- Mud Flaps
- Tailboard Mounted D-Rings
- Back-Up Alarm
- Power Fold for Stinger Storage
- Self Centering Crossbar with 3" Pivot Pin
- Roller Guided Hose Tracking System

Optional Features

- Clutch Pump
- Aluminum, Composite, or PolyBilt Modular Body
- Tow Sling (311 & 312 only)
- Motorcycle Attachment
- 24" Tunnel Toolbox for 84" C.A.
- Steel Light Pylon
- Aluminum Tubular Light Pylon
- Go-Jak Mounting Brackets
- Dolly Bunks
- Trailer Ball Adapter
- Emergency Lighting
- Work Lights
- Front Push Bumper
- Other Popular Century Options

Boom Specifications

Century 301 Express

At Boom Swivel	16,000 lbs.
Maximum Boom Elevation	33°

Century 311/312 Express

Lift Height at Maximum Elevation	
Retracted	78"
Extended	111"
Reach Past Tailgate	
Minimum Elevation (Extended)	50"
Maximum Elevation (Extended)	22"
Boom Rating at Boom Swivel	
Retracted	16,000 lbs.
Extended	4,000 lbs.

Wheel-Lift Specifications

Retracted Distance from Tailgate	
At Normal Tow Position	52"
Extended Distance from Tailgate	
At Normal Tow Position	85 1/2"
Maximum Hydraulic Extension	33 3/4"
Lift Rating	4,000 lbs.
Tow Rating	7,500 lbs.

Winch Rating & Cable

Rating (first layer of drum) each Winch	8,000 lbs.
Diameter and Length (each winch)	3/8" x 100'
Type	6 x 19 Hemp Center, IPS

Chassis Recommendation

GVWR	15,000 - 19,000 lbs.
Minimum Cab to Axle (Clear)	60"
Maximum Cab to Axle (Clear)	84"

CENTURY®

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.



Some optional equipment shown.