

# **Vulcan**<sup>®</sup>

## **810 Intruder**



*Some optional equipment shown.*

- **88"- 94" Modular Body Design**
- **Designed for Superior Visibility**
- **Spacious Tool Compartments**
- **8,000 lb. Recovery Boom**
- **7,500 lb. Tow Rating**

[millerind.com](http://millerind.com)





## Standard Features

- 60" C.A. Steel Modular Body
- Adjustable Body Width, 88" or 94"
- Auto Load Wheel Lift System
- 180° Pivoting Crossbar
- Self Centering Crossbar
- Tailboard Safety Chain Pockets
- Safety Chains
- Safety Chain Pocket Guards
- Wheel Lift Ratchets & Straps
- Driver & Passenger Side Tool Compartments
- In Cab Wheel Lift & Winch Controls
- 8,000 lb. Planetary Winch with 100' of 3/8" Cable
- Junction Box and Wiring Harness
- Mud Flaps
- Tailboard Mounted D-Rings
- Federal Standard 108 Lighting
- Tire Spacers (Flat Tires)

## Optional Features

- Clutch Pump or Pump/PTO
- Aluminum, Composite, or PolyBilt Modular Body
- Power Tilt with Adjustable limiter switches on elevation & tilt functions
- Steel Light Pylon
- Aluminum Tubular Light Pylon
- 24" Tunnel Tool Box
- Trailer Hitch Attachment
- Motorcycle Attachment
- Dress Up Packages
- Emergency Lighting
- Dollies & Mounting Options
- Trailer Hitch Attachment

## Specifications

### BOOM

Recovery Boom (at boom end swivel)	. 8,000 lbs.
Maximum Lift Angle	..... 21°
Winch (Planetary)	..... 8,000 lbs.
Cable	..... 3/8" x 100'

### UNDERLIFT

Lift Capacity Extended	..... 4,000 lbs.
Tow Rating	..... 7,500 lbs.
Maximum Reach	..... 73"
Optional Power Tilt	..... 30° Arc

### CHASSIS RECOMMENDATIONS

Minimum C.A. (Cab to Axle)	..... 60"
Maximum C.A. (With Tunnel Tool Box)	..... 84"
Suggested GVWR	..... 14,500 lbs.



The optional motorcycle attachment provides a quick and convenient hook-up for those times when a motorcycle tow is needed .

The optional Power Tilt feature on the Intruder allows the wheel lift to operate through a 30-degree arc, which provides easier hook-ups on driveways or sloped roads.



All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.