



V-30 G2 Heavy Duty



Some optional equipment shown.

- *Versatile, Medium Duty Power*
- *Dual 15,000 lb. Winches*
- *32,000 lb. Retracted Boom*
- *12,000 lb. Retracted Underlift*
- *Low Profile VX2 Body Option*

Standard Features

- 120" CA or 136" CA Aluminum Modular Body
- Three Compartments Per Side
- Pass Thru Tunnel Box
- Lift Fork Storage, Driver & Passenger Side
- Adjustable Shelves
- Manual Controls - Driver's and Passenger Side
- Passenger Side Lanyard Control for Underlift
- Hydraulic Rear Jacks with Flipper Feet
- Tailboard D-Rings
- Safety Chains in the Tailboard
- Dual 15,000 lb. Planetary Winches
- Winch Air Free Spool
- 360 Degree Sheave Heads
- Cable Tensioners
- Hydraulic Pump
- 4 Sets of Lift Forks
- 5,000 lb. & 6,500 lb. Strapless Wheel Retainers
- Chrome Latches with Keyless Lock/Unlock
- LED Body Lighting
- LED Tool Compartment Lighting
- Gas Door Shocks
- Mud Flaps
- Air & Electrical Hookups

Optional Features

- 120" or 138" VX2 Low Profile Body
- Light Pylon
- In Cab Controls
- Additional Lifting Attachments
- Wireless Remote
- Manual Extension Rear Outriggers
- Emergency Lighting
- Air Shift PTO
- Work Lights
- Wide Load Light Bar
- Hand Rails
- Installation

Underlift Specifications

Retracted with Forks	12,000 lbs.
Extended with Forks	8,500 lbs.
Extended with Wheel Retainers . . .	5,000 lbs. / 6,500 lbs.
Maximum Reach to Center of Forks	
At the Normal Tow Height	84"
Positive Tilt	20°
Negative Tilt	10°
Tow Rating	32,000 lbs.

Boom Specifications

Retracted at 30°	32,000 lbs.
Extended at 30°	12,000 lbs.
Maximum Lift Angle	36°
Maximum Hook Height	160"
Reach Past Tailboard at 30°	54"

Winch Rating & Cable

Rating (first layer of drum) each Winch	15,000 lbs.
Diameter and Length (each winch)	½" x 150'
Cable Type	6 x 37 IWRC

Chassis Recommendations

GVWR	26,500 - 31,000 lbs.
Maximum Frame Height	40"
Maximum Tire Size	275/80 R 22.5
Minimum Cab to Axle (Clear)	120"
Maximum Cab to Axle (Clear)	138"

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.



Optional VX2 Low Profile Body



Some optional equipment shown.