



Increase your profits with the New Miller Industries Towing Service Vehicle. Capable of hauling up to 36 Batteries, Electric Air Compressor, Floor Jack, Gas Cans, Dollies, Jumper Cables and much, much more along with providing towing capabilities with the Holmes 220 Snatcher auto load wheel lift system. (Also available without the Tow Unit as a Light Service Vehicle)



Make All Your Light Duty Service Calls Profitable

STANDARD EQUIPMENT

- Two Aluminum 48"x34"x23" Locking Front Compartments will accommodate approximately 36 Automotive Batteries; Upper Shelf for small tools
- One Aluminum 48"x34"x20" Rear Module Compartment to store Equipment for Jump Starts, Tire Service, Lock-Outs, Repair and Light-Duty Towing
- 1 Open Modular Tray (48" x 34" x 4") Designed to Store Self-Loading Dollies, (2) GoJak®, (2) Pails for Floor Dry and Waste, (2) Plastic Fuel Cans, Emergency Cones, Broom, Shovel, Sledge Hammer, and Pry-Bar Holder. (Equipment and Mounting Brackets Optional)
- Poly Liner for the Floor and Lower Portion of the Enclosed Compartments and Open Top Tray
- Built-In Divider Frame with 1" Intervals with 5 Dividers included in each Enclosed Module
- Modular Fender Skirts
- Powder-Coated Ford Z1 Oxford White Standard on exterior of Modular Compartments and Tray

- Mud-Flap Mounting Brackets
- Rear Bumper with Junction Box, LED Stop/Tail/Turn-Lights, LED Marker Lights, License Plate Light, LED Rear Flood/Backup Lights, Backup Alarm, accommodations for 7-Wire RV Plug and 4-Wire Tow Light Socket
- Braided Wiring Harness
- 12 Volt Air Compressor Package, ¼" x 50' Hose and Reel, and Aluminum Storage Well
- 4 Corner LED Flashing Lights with Chrome Bezels
- *Holmes 220 Snatcher with Hydraulic Auto loading Wheel lift
- *Electric/Hydraulic Power Unit
- *4 Function Remote Control Pendant Cord
- *Wheel Lift Straps
- *Safety Chains in Rear Bumper
- *Group 27 Auxiliary Dry Cell Battery with Storage Box
- *Electrical Solenoid and Wiring for Circuit protection
- *Anti-Spray Panels to attach to the underside of the Holmes 220

(*NOT INCLUDED WITH LIGHT SERVICE VEHICLE)

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and of specifications without notice or obligation. Some equipment shown is optional.

8503 Hilltop Drive • Ooltewah, TN 37363
 800-489-2401 • 423-238-7227
 Fax 800-960-6667 • www.MillerInd.com



800-222-6047

www.zips.com

OPTIONAL SERVICE ACCESSORY AND TOOL PACKAGE

Deck Mounted Tool Holder with 8 lb Sledge Hammer,
Jumbo Pry Bar, Extendable Broom and Square Point Shovel

3 - Traffic Cones 18" w/Reflective

Deck Mounted Cone Storage

Double Gas Can holder

2 Red Two Gallon Gas Cans

2 - Four Gallon Trash Cans with Lids

2 - Deck Mounted Trash Can Mounts

400 AMP Plug-in Jumper Cable Kit

Jumper Cable Holder

Jumper Cable Plug-in Connections (1 Front and 1 Rear)

600 AMP Portable Jump Starter Pack

HD Battery Carrier

Battery Terminal Cleaner

Fire Extinguisher & Mounting Bracket

Triangle Reflector Kit

First Aid Kit

18V Rechargeable 1/2" Impact Wrench 400 ft/lbs

Rechargeable Flashlight

1/2" Torque Wrench

11 Piece 1/2" Drive Socket Set

2 - Wheel Chocks

Vinyl Clean Pad

4 Way Lug Wrench

3 Ton Aluminum Floor Jack

1.5 Ton Jack Stand

Lock Out Tool Kit with Big Easy Stick and Wedge

ADDITIONAL EQUIPMENT INCLUDED WITH OPTIONAL TOWING ACCESSORY PACKAGE

Self Loading Dollies & Aluminum Wheels and Axles

Dolly & Axle Mounting Brackets

Dolly Safety Straps

Model 6,200 GoJak® Dollies 1,550 lbs (pair)

GoJak® Mounting Brackets

TowMate, 15" Wireless, Hardwired Tow Light Kit
& Hardwired Transmitter

OTHER AVAILABLE OPTIONS

Front Push Bumper

Trailer Hitch Bracket for use w/220 Snatcher

Auxiliary Spring Kit



CHASSIS RECOMMENDATIONS

TOWING SERVICE VEHICLE

Body width 90" or 95.5"

Dual Rear Wheels

60" CA

Minimum GVW 13,200 lbs

Maximum frame height 37.5"

A front push bumper or extended cab is recommended to
improve towing capabilities

LIGHT SERVICE VEHICLE

Single or Dual Rear Wheels

56" or 60" CA

Minimum GVW 8,600 lbs

Body Width 78", 90" or 95"

